

# Indicies

p-n-i-n- Transistor	3617
p-n- Phototransistor	3616
p-n-p-n- Diode	1408
p-n-p-n- Transistor	3622
p-n-p- Transistor	3620
p-n-p- Übergangszone	3619
p-n- Übergangszone	3615

\* \* \*

Facsimile call time series, 136	
phase A, 136, 137-39	
phase B, 136, 137-39	
phase C, 136, 139-41	
phase D, 136, 141	
phase E, 136, 141	

\* \* \*

Schmitt Trigger	10-20 to 10-27
Series Peaking	5-9 to 5-11
Shunt capacitance, square-wave testing	2-11, 2-12
Shunt peaking	5-6 to 5-9
Signal-current requirements	8-12 to 8-14
Single-sweep feature	11-24 to 11-27

\* \* \*

ionenlaag	2655
ionenlawine	2634
ionenmicroscop met vedenmissie	1901
ionenmigratie	2650
ionenmotor	2645
ionenopbrengst	2660
ionenopeenhoping	2638
ionenpaar	2652
ionenpaaropbrengst	2653
ionenroosterstroom	2640

\* \* \*

Output resistance:  
 cascode, 47  
 chopper channel, 158  
 common-emitter, 100  
 common-mode, 22,27  
 common-source, 101  
 differential, 7, 9  
 dynamic load, 50  
 emitter-follower, 98  
 operational amplifier, 120, 447  
 source-follower, 99  
 totem pole, 108

\* \* \*

triode-heptodo	4917
triode-hexodo	4918
triode-pentodo	4920
triple diodo	4923

\* \* \*

MIL-C-2607	5-44, 5-57
MIL-F-14256	12-3, 14-6
MIL-G-45204	5-31, 5-34, 5-41, 5-57
MIL-I-46058	10-18 to 10-26
MIL-P-13949	2-7, 2-14 to 2-16, 2-18, 2-23, 5-3, 5-57
MIL-P-55110	2-9, 5-42, 5-47, 5-48, 5-57, 14-16
MIL-STD-275	5-4, 5-31, 5-35, 5-41, 5-42, 5-48, 5-57 to 5-59, 8-12, 10-16
MIL-STD-429	5-3, 5-57

\* \* \*

tracks, 17-20  
 eight, 18  
 four, 18  
 half, 18  
 two, 18

\* \* \*

- Loudspeakers, 380-382, 416-424
  - acoustic labyrinth for, 422-423
  - baffles for, 420-424
    - need for, 420-422
  - bass-reflex baffle for, 422
  - coaxial, 417
  - cone of, 416
  - crossover network for, 419-420

\* \* \*

- tri-state, 68
- truth table, 144
  - 1-of-2 decoder, 177
  - 4-bit addressable latch, 187
  - 4-bit addressable register (PLS), 192
  - 4-bit barrel shifter, 196
  - 4-bit registered magnitude comparator, 193
  - 4-bit universal shift register, 195
  - 4-input multiplexer, 179
  - 4-input parity generator, 182
  - 4-input priority encoder, 178
  - AND gate, 170
  - AND-OR-INVERT gate, 172
  - bit counting circuit, 76
  - combination lock example, 39
  - D-latch, 50, 185
  - D-type flip-flop, 50, 188
  - divide-by-5 ripple counter, 197
  - exclusive-OR gate, 173
  - J-K flip-flop, 51, 189
  - Johnson counter, 202
  - magnitude comparator, 181
  - memory map example, 70
  - NAND gate, 170
  - NOR gate, 171
  - open collector, 174
  - OR gate, 40, 171
  - R-S flip-flop, 51
  - R-S latch, 50, 186
  - transceiver, 175
  - tri-state buffer, 174
  - up/down decade counter, 201
- truth table entry, 75

\* \* \*

Attenuators, 353-71  
distributed thin film, 356-7  
fixed-waveguide, 363  
flap, 361  
lossy-line, 355  
nonreciprocal, 367-71  
pi-circuits, 354-55  
piston, 358-59  
rotary-vane, 362-63  
side-vane, 361-62  
step, 357-58, 360-61  
“T” circuits, 353-54  
Atwater, H. A., 71

\* \* \*

S-model-verzwakker	3062
smoorgroef	702
smoorgroefflens	703
smoorgroefkoppeling	704
sneeuw	4408